



# POLY64204 – POWER BLAST CONCRETE AND DRIVEWAY CLEANER

### **SECTION 1: IDENTIFICATION**

1.1 PRODUCT IDENTIFIER

Product name Power Blast Concrete and Driveway Cleaner

Product number POLY64204 (Gal)

Brand PolyGuard

1.4 SUPPLIER'S DETAILS

Name Highline Aftermarket Address 4500 Malone Road Memphis TN 38118

Telephone 901-775-5555

email sds@highlineaftermarket.com

1.5 EMERGENCY PHONE NUMBER(S) CHEM-TEL (800) 255-3924

24 Hour Assistance

# **SECTION 2: HAZARD IDENTIFICATION**

#### General hazard statement

"Consumer Products", as defined by the US Consumer Product Safety Act and which are used as intended (typical consumer duration and frequency), are exempt from the OSHA Hazard Communication Standard (29 CFR 1910.1200). This SDS is being provided as a courtesy to help assist in the safe handling and proper use of the product.

#### 2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS classification in accordance with: (US) OSHA (29 CFR 1910.1200)

- Sensitization, skin, Cat. 1
- Acute toxicity, dermal, Cat. 3
- Acute toxicity, inhalation, Cat. 3
- Acute toxicity, oral, Cat. 3
- Carcinogenicity, Cat. 1B
- Germ cell mutagenicity, Cat. 1B
- Skin corrosion/irritation, Cat. 3
- Specific target organ toxicity (single exposure), Cat. 1
- Toxic to reproduction, Cat. 1B
- Carcinogenicity, Cat. 2

### 2.2 GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

Signal word Danger





POLY64204- POWER BLAST CONCRETE & DRIVEWAY CLEANER

## **Pictogram**



#### 1. Exclamation mark; 2. Health hazard

Hazard	statement(s)
11004	

H301 Toxic if swallowed
H311 Toxic in contact with skin

H317 May cause an allergic skin reaction

H331 Toxic if inhaled

H340 May cause genetic defects [route]

H350 May cause cancer [route]

H351 Suspected of causing cancer [route]

H360 May damage fertility or the unborn child [effect, route]

H370 Causes damage to organs [organs, route]

### Precautionary statement(s)

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor

P302+P352 IF ON SKIN: Wash with plenty of water

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor P308+P313 IF exposed or concerned: Get medical advice/attention.

P311 Call a POISON CENTER/doctor

P312 Call a POISON CENTER/doctor if you feel unwell.

P330 Rinse mouth.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P361+P364 Take off immediately all contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container to proper receptacle.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2 MIXTURES

Components





POLY64204- POWER BLAST CONCRETE & DRIVEWAY CLEANER

1. Water

Concentration 20 - 90 % (volume)

CAS no. 7732-18-5

2. 2-Butoxyethanol

 Concentration
 < 3 % (weight)</td>

 EC no.
 203-905-0

 CAS no.
 111-76-2

 Index no.
 603-014-00-0

- Skin corrosion/irritation, Cat. 2

- Serious eye damage/eye irritation, Cat. 2

Acute toxicity, dermal, Cat. 4
Acute toxicity, inhalation, Cat. 4
Acute toxicity, oral, Cat. 4

H302 Harmful if swallowed
H312 Harmful in contact with skin
H315 Causes skin irritation
H319 Causes serious eye irritation

H332 Harmful if inhaled

3. Isopropanol

 Concentration
 < 2 % (weight)</td>

 EC no.
 414-810-0

 CAS no.
 67-63-0

 Index no.
 607-403-00-6

Flammable liquids, Cat. 2Eye damage/irritation, Cat. 2A

- Specific target organ toxicity (single exposure), Cat. 3

H225 Highly flammable liquid and vapor
H319 Causes serious eye irritation
H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness

4. Sodium hydroxide

 Concentration
 < 1 % (weight)</td>

 EC no.
 215-185-5

 CAS no.
 1310-73-2

 Index no.
 011-002-00-6

- Skin corrosion/irritation, Cat. 1A

H314 Causes severe skin burns and eye damage

## 5. 4,4'-Methylene-bis(2-chloroaniline)





POLY64204- POWER BLAST CONCRETE & DRIVEWAY CLEANER

 Concentration
 < 1 % (weight)</td>

 EC no.
 202-918-9

 CAS no.
 101-14-4

 Index no.
 612-078-00-9

- Carcinogenicity, Cat. 1B - Acute toxicity, oral, Cat. 4

- Hazardous to the aquatic environment, short-term (acute), Cat. 1 - Hazardous to the aquatic environment, long-term (chronic), Cat. 1

H302 Harmful if swallowed
H350 May cause cancer [route]
H400 Very toxic to aquatic life

H410 Very toxic to aquatic life with long lasting effects

Trade secret statement (OSHA 1910.1200(i))

21

### **SECTION 4: FIRST-AID MEASURES**

#### 4.1 DESCRIPTION OF NECESSARY FIRST-AID MEASURES

General advice Consult a physician. Show this safety data sheet to the doctor in attendance.

Move out of dangerous area.

If inhaled Call a poison center or doctor if you feel unwell.

Acute and delayed symptoms and effects: May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache,

hoarseness, and nose and throat pain.

In case of skin contact Rinse with plenty of water. Call a doctor if irritation develops or persists.

Acute and delayed symptoms and effects: May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

In case of eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Call a doctor if you feel unwell.

Acute and delayed symptoms and effects: May cause eye irritation.

Signs/symptoms may include redness, swelling, pain, tearing, and blurred or

hazy vision.

If swallowed Rinse mouth. If vomiting occurs naturally, have victim lean forward to

reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious

person. Call a poison center or doctor immediately

Acute and delayed symptoms and effects: Harmful if swallowed.





POLY64204- POWER BLAST CONCRETE & DRIVEWAY CLEANER

#### 4.2 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY Treat symptomatically.

### **SECTION 5: FIRE-FIGHTING MEASURES**

#### 5.1 SUITABLE EXTINGUISHING MEDIA

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

#### 5.2 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

Methanol: Carbon oxides

### 5.3 SPECIAL PROTECTIVE ACTIONS FOR FIRE-FIGHTERS

Wear self-contained breathing apparatus for firefighting if necessary.

#### **Further information**

Use water spray to cool unopened containers.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protective equipment as described in Section 8. Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Evacuate personnel to safe areas.

#### 6.3 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

#### Reference to other sections

For disposal see section 13.

### **SECTION 7: HANDLING AND STORAGE**

#### 7.1 PRECAUTIONS FOR SAFE HANDLING

Use personal protective equipment as required. Keep container closed when not in use. Never return spills in original containers for re-use. Keep out of the reach of children.

#### 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### Specific end use(s)

Apart from the uses mentioned in section 1 no other specific uses are stipulated.





POLY64204- POWER BLAST CONCRETE & DRIVEWAY CLEANER

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 CONTROL PARAMETERS

1. 2-Butoxyethanol (CAS: 111-76-2 EC: 203-905-0)

PEL (Inhalation): 50 ppm (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 240 mg/m3 (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 20 ppm (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 5 ppm (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 20 ppm

97 mg/m3

California permissible exposure limits for chemical contaminants

(Title 8, Article 107)/Skin

TWA (Inhalation): 50 ppm 240 mg/m3; USA (OSHA)

USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air

Contaminants/Skin designation
The value in mg/m3 is approximate

TWA (Inhalation): 5 ppm 24 mg/m3; USA (NIOSH)

USA. NIOSH Recommended Exposure Limits/Potential for dermal absorption

TWA (Inhalation): 20 ppm; USA (ACGIH)

USA. ACGIH Threshold Limit Values (TLV)/Upper Respiratory Tract irritation Eye irritation Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Confirmed animal carcinogen with unknown relevance to humans

TLV® (Inhalation): 20 ppm; USA (ACGIH) OSHA Annotated Table Z-1, www.osha.gov

# 2. Isopropyl alcohol (CAS: 67-63-0)

PEL (Inhalation): 400 ppm (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 980 mg/m3 (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 400 ppm, (ST) 500 ppm (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 400 ppm, (ST) 500 ppm (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

TLV® (Inhalation): 200 ppm, (ST) 400 ppm; USA (ACGIH)

OSHA Annotated Table Z-1, www.osha.gov

3. Sodium hydroxide (CAS: 1310-73-2)





POLY64204- POWER BLAST CONCRETE & DRIVEWAY CLEANER

PEL (Inhalation): 2 mg/m3; USA (OSHA) OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): (C) 2 mg/m3; USA (Cal/OSHA) OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): (C) 2 mg/m3; USA (NIOSH) OSHA Annotated Table Z-1, www.osha.gov

TLV® (Inhalation): (C) 2 mg/m3; USA (ACGIH) OSHA Annotated Table Z-1, www.osha.gov

#### 8.2 APPROPRIATE ENGINEERING CONTROLS

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, gas, etc.) below recommended exposure limits.

### 8.3 INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT (PPE)

### **Pictograms**





### Eye/face protection

No special protective equipment required for normal use. Safety glasses are recommended for industrial use of if splash hazard .

### Skin protection

Not required for normal product use.

#### **Body protection**

Wear protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### Respiratory protection

Not required under normal use conditions. Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Thermal hazards

No data available.

### **Environmental exposure controls**

Do not let product enter drains.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties





POLY64204- POWER BLAST CONCRETE & DRIVEWAY CLEANER

Appearance/form (physical state, color, etc.)

Clear Liquid

Odor Mild

Odor threshold No data available.

pH Alkaline

Melting point/freezing point

No data available.

No data available.

No data available.

Flash point 200 F

Evaporation rate

Flammability (solid, gas)

Upper/lower flammability limits

Upper/lower explosive limits

Vapor pressure

Vapor density

No data available.

Relative density 8.58 lbs/gal

Solubility(ies)

Partition coefficient: n-octanol/water

Auto-ignition temperature

No data available.

No data available.

No data available.

Auto-ignition temperature No data available. Decomposition temperature No data available.

Viscosity No data available.

Explosive properties

No data available.

Oxidizing properties

No data available.

#### SECTION 10: STABILITY AND REACTIVITY

### 10.1 REACTIVITY

Contact with incompatible materials. Sources of ignition. Exposure to heat.

### 10.2 CHEMICAL STABILITY

Stable under normal storage conditions.

### 10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No data available.

### 10.4 CONDITIONS TO AVOID

Heat, flames and sparks. Incompatible products. Keep away from open flames, hot surfaces and sources of ignition.

#### 10.5 INCOMPATIBLE MATERIALS

2-Butoxyethanol: Strong oxidizing agents

Methanol: Acid chlorides, Acid anhydrides, Oxidizing agents, Alkali metals, Reducing agents, Acids

Diethanolamine: Oxidizing agents, Copper, Zinc, Iron

Ethanol: Alkali metals, Oxidizing agents, Peroxides

Glycerine: Strong bases, Strong oxidizing agents

Isopropanol: Oxidizing agents, Acid anhydrides, Aluminium, Halogenated compounds, Acids





POLY64204- POWER BLAST CONCRETE & DRIVEWAY CLEANER

Sodium hydroxide: Caustic soda reacts with all the mineral acids to form the corresponding salts. It also reacts with weak-acid gases, such as hydrogen sulfide, sulfur dioxide, and carbon dioxide. Caustic soda reacts with amphoteric metals (Al, Zn, Sn) and their oxides to form complex anions such as AlO2(-), ZnO2(-2), SNO2(-2), and H2 (or H2O with oxides). All organic acids also react with sodium hydroxide to form soluble salts. Another common reaction of caustic soda is dehydrochlorination.

#### 10.6 HAZARDOUS DECOMPOSITION PRODUCTS

No data available.

2-Butoxyethanol: Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

Diethanolamine: Other decomposition products - No data available

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Nitrogen oxides (NOx)

In the event of fire: see section 5

Sodium hydroxide: Sodium oxides

### SECTION 11: TOXICOLOGICAL INFORMATION

#### Information on toxicological effects

### **Acute toxicity**

Symptoms (including delayed and immediate effects):

Inhalation: May cause respiratory irritation. Signs/symptoms may include cough, sneezing,nasal discharge,

headache, hoarseness, and nose and throat pain.

Ingestion: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset,

nausea, vomiting and diarrhea.

ATE (dermal) of mixture: 378.44 mg/kg

ATE (inhalation, gaseous) of mixture: 884.33 ppmv

ATE (oral) of mixture: 126.26 mg/kg

----

Ethanol: ACGIH: A3 Confirmed animal carcinogen with unknown relevance to humans.

### Skin corrosion/irritation

May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

### Serious eye damage/irritation

May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Respiratory or skin sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled

#### **Additional information**

No data available.





POLY64204- POWER BLAST CONCRETE & DRIVEWAY CLEANER

### SECTION 12: ECOLOGICAL INFORMATION

#### **Toxicity**

No data available on product

## Persistence and degradability

No data available on product

#### Bioaccumulative potential

No data available on product

# Mobility in soil

No data available.

#### Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### Other adverse effects

No data available.

### SECTION 13: DISPOSAL CONSIDERATIONS

### Disposal of the product

Disposal should be in accordance with applicable Federal, State and local laws and regulations. Local regulations may be more stringent than State or Federal requirements.

### Disposal of contaminated packaging

Dispose of as unused product.

# **SECTION 14: TRANSPORT INFORMATION**

DOT (US)

Not dangerous goods

IMDG

Not dangerous goods

**IATA** 

Not dangerous goods

### SECTION 15: REGULATORY INFORMATION

### 15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS SPECIFIC FOR THE PRODUCT IN QUESTION





POLY64204- POWER BLAST CONCRETE & DRIVEWAY CLEANER

California Prop. 65 Components

Chemical name: 4,4'-Methylene-bis(2-chloroaniline)

CAS number: 101-14-4 07/01/1987 - Cancer

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## **Massachusetts Right To Know Components**

Ethylene glycol monobutyl ether

CAS: 111-76-2

Isopropyl alcohol CAS number: 67-63-0

Chemical name: Sodium hydroxide

CAS number: 1310-73-2

Chemical name: 4,4'-Methylenebis(2-chloroaniline)

CAS number: 101-14-4

### **New Jersey Right To Know Components**

Ethylene glycol monobutyl ether

CAS: 111-76-2

Isopropyl alcohol CAS number: 67-63-0

Common name: SODIUM HYDROXIDE

CAS number: 1310-73-2

Common name: 4,4'-METHYLENE BIS (2-CHLOROANILINE)

CAS number: 101-14-4

## Pennsylvania Right To Know Components

Ethylene glycol monobutyl ether

CAS: 111-76-2

Isopropyl alcohol CAS number: 67-63-0

Chemical name: Sodium hydroxide

CAS number: 1310-73-2

Chemical name: Benzenamine, 4,4'-methylenebis[2-chloro-

CAS number: 101-14-4

## **SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.





POLY64204- POWER BLAST CONCRETE & DRIVEWAY CLEANER

#### SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Acute Health Hazard

### **SARA 313 Components**

The following components are subject to reporting levels established by SARA Title III, Section 313: Ethylene glycol monobutyl ether

CAS: 111-76-2

The following components are subject to reporting levels established by SARA Title III, Section 313: Isopropyl alcohol

CAS number: 67-63-0

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## **SECTION 16: OTHER INFORMATION**

#### 16.1 FURTHER INFORMATION/DISCLAIMER

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. In no event shall Highline Aftermarket be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if Highline Aftermarket has been advised of the possibility of such damages.

Prepared By Mark Kozak

Version: 1.1, 9/9/2020, p. 12 of 12