

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9199

1. Identification of the Substance / Preparation and of the Company / Undertaking

Product identifier

Product Name RAIN-X Deicer Spray Aerosol**Stock Numbers** 113569 / RX44014

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Windshield Deicer - Aerosol**Uses advised against** No information available

Details of the supplier of the safety data sheet

Supplier Name Highline Aftermarket
Supplier Address 4500 Malone Road
Memphis, TN 38118
US**Supplier Phone Number** Phone: (901) 775-5555
sds@highlineaftermarket.com**Emergency Tel**Highline Aftermarket CHEMTREC: (800) 424-9300
4500 Malone Road Memphis, TN 38118
US
Phone: (901) 775-5555 sds@highlineaftermarket.com
CHEMTREC: (800) 424-9300 phone Number

2. Hazards Identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 3
Acute toxicity - Dermal	Category 3
Acute toxicity - Inhalation (Vapors)	Category 3
Acute toxicity - Inhalation (Dusts/Mists)	Category 3
Specific target organ toxicity (single exposure)	Category 1

Issuing Date: 1-Jun-2008


Revision Date: 27-Mar-2015

SDS Number: 9199

Flammable Aerosols	Category 1
Gases under pressure	Compressed gas

GHS Label elements, including precautionary statements

Emergency Overview

<p>Signal Word</p> <p>Hazard Statement:</p> <ul style="list-style-type: none"> - Toxic if inhaled - Causes damage to organs - Extremely flammable aerosol - Contains gas under pressure; may explode if heated <p>Appearance Clear</p>	<p>Danger</p>  <p>Physical State Liquid Spray Aerosol</p>	<p>Odor Mild</p>
---	--	-------------------------

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Wear protective gloves/protective clothing/eye protection/face protection
 Use only outdoors or in a well-ventilated area
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Pressurized container. Do not pierce or burn, even after use
 Do not spray on an open flame or other ignition source.

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician
 Specific treatment (see supplemental first aid instructions on this label)

Skin

Call a POISON CENTER or doctor/physician if you feel unwell
 Wash contaminated clothing before reuse
 IF ON SKIN wash with plenty of soap and water
 Remove/take off immediately all contaminated clothing

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a POISON CENTER or doctor/physician

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9199

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
Rinse mouth

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

4.4% of the mixture consists of ingredient(s) of unknown toxicity

Other information

PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. Composition / Information on Ingredients

Chemical Name	CAS No	Weight-%	Trade Secret
Methyl alcohol	67-56-1	60 - 100	*
Silane	7803-62-5	3 - 7	*
Propylene Glycol	57-55-6	3 - 7	*
Carbon Dioxide	124-38-9	1 - 5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. First Aid Measures

First aid measures

General Advice Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9199

- Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Seek immediate medical attention/advice.
- Skin Contact** In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
- Inhalation** Move victim to fresh air. Give artificial respiration if victim is not breathing. Administer oxygen if breathing is difficult.
- Ingestion** Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.
- Self-protection of the first aider** Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects Coughing and/ or wheezing. Difficulty in breathing.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Keep victim warm and quiet.

5. Fire-fighting Measures

Suitable Extinguishing Media

Use extinguishing agent suitable for type of surrounding fire. Dry chemical, CO₂, water spray fog or regular foam. Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

Unsuitable extinguishing media

Do not extinguish a leaking gas fire unless leak can be stopped.

Specific Hazards Arising from the Chemical

Some may burn but none ignite readily. Ruptured cylinders may rocket.

Uniform Fire Code Aerosols: Level II

Hazardous Combustion Products

Carbon oxides.

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9199

Explosion Data**Sensitivity to Mechanical Impact** Yes**Sensitivity to Static Discharge** Yes**Protective equipment and precautions for firefighters**

Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures**Personal Precautions** Stop leak if you can do it without risk. Do not touch or walk through spilled material.**Other Information** Ventilate the area.**Environmental Precautions****Environmental Precautions** Prevent entry into waterways, sewers, basements or confined areas. Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.**Methods and material for containment and cleaning up****Methods for Containment** If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.**Methods for cleaning up** Do not direct water at spill or source of leak.

7. Handling and Storage

Precautions for safe handling**Handling** Handle in accordance with good industrial hygiene and safety practice. Contents under pressure. Do not puncture or incinerate cans. Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with eyes. Avoid breathing vapors or mists.

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9199

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Protect from moisture. Store away from other materials. Store locked up. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products None known based on information supplied.

8. Exposure Controls / Personal Protection

Control parameters

Exposure Guidelines

Chemical	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methyl alcohol 67-56-1	STEL = 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 325 mg/m ³ STEL: 250 ppm
Silane 7803-62-5	TWA: 5 ppm	(vacated) TWA: 5 ppm (vacated) TWA: 7 mg/m ³	TWA: 5 ppm TWA: 7 mg/m ³
Carbon Dioxide 124-38-9	STEL = 30000 ppm TWA: 5000 ppm	TWA: 5000 ppm TWA: 9000 mg/m ³ (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m ³ (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m ³	IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m ³ STEL: 30000 ppm STEL: 54000 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9199

Appropriate engineering controls

Engineering Measures Showers
 Eyewash stations
 Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Tight sealing safety goggles.

Skin and Body Protection Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant apron. Impervious gloves. Antistatic boots.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. No information available. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not breathe the vapor or mist. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and Chemical Properties

Physical and Chemical Properties

Physical State	Liquid Spray, Aerosol	Odor	Mild
Appearance	Clear	Odor Threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	Unknown	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9199

Specific Gravity	No data available	None known
Water Solubility	Completely soluble	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Explosive properties	No data available	None known
Oxidizing Properties	No data available	None known

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

10. Stability and Reactivity

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Excessive heat. Heat, flames and sparks.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

Carbon oxides.

11. Toxicological Information

Information on likely routes of exposure

Product Information

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9199

- Inhalation** Specific test data for the substance or mixture is not available. Toxic by inhalation. (based on components).
- Eye Contact** Specific test data for the substance or mixture is not available.
- Skin Contact** Specific test data for the substance or mixture is not available. Toxic in contact with skin. May be absorbed through the skin in harmful amounts. (Based on components).
- Ingestion** Specific test data for the substance or mixture is not available. May be harmful if swallowed. (based on components).

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl alcohol 67-56-1	= 5628 mg/kg (Rat)	-	= 83.2 mg/L (Rat) 4 h
Silane 7803-62-5	-	-	= 9600 ppm (Rat) 4 h
Propylene Glycol 57-55-6	= 20000 mg/kg (Rat)	= 20800 mg/kg (Rabbit)	-

Information on toxicological effects

Symptoms Coughing and/ or wheezing. Difficulty in breathing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity Contains no ingredient listed as a carcinogen.

Reproductive Toxicity No information available.

STOT - single exposure Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). If this product is a mixture, the classification is not based on toxicology studies for this product, but is based solely on toxicology studies for ingredients found within this product. Detailed substance and/or ingredient information may be provided in other sections of this SDS. Target organs effects listed in this document may result from a single overexposure to this product. Causes damage to organs if swallowed. Causes damage to organs in contact with skin.

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9199

STOT - repeated exposure	No information available.
Chronic Toxicity	Effects from this product caused by acute exposure may cause permanent damage to target organs and/or may cause chronic conditions.
Target Organ Effects	Respiratory system. Systemic Toxicity. Central Nervous System (CNS). Central Vascular System (CVS). Eyes. Gastrointestinal tract (GI). Skin. Lungs.
Aspiration Hazard	No information Available

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 135.00 mg/kg

ATEmix (dermal) 405.00 mg/kg (ATE)

ATEmix (inhalation-dust/mist) 0.68 mg/l

ATEmix (inhalation-vapor) 4.00 ATEmix

12. Ecological Information

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Methyl alcohol 67-56-1		96h LC50: = 28200 mg/L (Pimephales promelas) 96h LC50: > 100 mg/L (Pimephales promelas) 96h LC50: 19500 - 20700 mg/L (Oncorhynchus mykiss) 96h LC50: 18 - 20 mL/L (Oncorhynchus mykiss) 96h LC50: 13500 - 17600 mg/L (Lepomis macrochirus)	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9199

Propylene Glycol 57-55-6	96h EC50: = 19000 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 51600 mg/L (Oncorhynchus mykiss) 96h LC50: 41 - 47 mL/L (Oncorhynchus mykiss) 96h LC50: = 51400 mg/L (Pimephales promelas) 96h LC50: = 710 mg/L (Pimephales promelas)	-	24h EC50: > 10000 mg/L 48h EC50: > 1000 mg/L
-----------------------------	--	--	---	---

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Methyl alcohol 67-56-1	-0.77

Other adverse effects

No information available.

13. Disposal Considerations

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR261).

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number U154 D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl alcohol 67-56-1		Included in waste stream: F039		U154

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Methyl alcohol 67-56-1	Toxic Ignitable

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9199

14. Transport Information

DOT

Proper Shipping Name	CONSUMER COMMODITY
Hazard Class	ORM-D
Description	CONSUMER COMMODITY, ORM-D
Emergency Response Guide Number	126

TDG

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Subsidiary Class	6.1
Description	UN1950, AEROSOLS, 2.1 (6.1)

MEX

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Description	UN1950, AEROSOLS, 2.1

ICAO

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Subsidiary Class	6.1
Description	UN1950, AEROSOLS, 2.1 (6.1)

IATA

UN-No.	UN1950
Proper Shipping Name	AEROSOLS, FLAMMABLE
Hazard Class	2.1
Subsidiary Class	6.1
Description	UN1950, AEROSOLS, FLAMMABLE 2.1 (6.1)

IMDG/IMO

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Subsidiary Class	6.1

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9199

EmS-No.	F-D, S-U
Description	UN1950, AEROSOLS, 2.1 (6.1)
<u>RID</u>	
UN-No.	UN0362
Proper Shipping Name	AEROSOLS, FLAMMABLE, CONTAINING SUBSTANCES IN DIVISION 6.1 PACKING GROUP II
Hazard Class	1.4
Classification code	1.4G
Description	UN0362, AEROSOLS, FLAMMABLE, CONTAINING SUBSTANCES IN DIVISION 6.1, PACKING GROUP II, 1.4
<u>ADR</u>	
UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1 6.1
Classification code	5T
Tunnel restriction code	(D)
Description	UN1950, AEROSOLS, 2.1 (6.1)
<u>ADN</u>	
UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Classification code	5T
Special Provisions	190, 327, 344, 625
Description	UN1950, AEROSOLS, 2.1 (6.1)
Hazard Labels	2.1 + 6.1
Limited Quantity	120 ML
Ventilation	VE02, VE04

15. Regulatory Information

International Inventories

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.
IECSC	-

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9199

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Methyl alcohol - 67-56-1	67-56-1	60 - 100	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	Yes
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Methyl alcohol 67-56-1	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Methyl alcohol - 67-56-1	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Methyl alcohol 67-56-1	X	X	X	X	X
Silane 7803-62-5	X	X	X		-
Propylene Glycol 57-55-6	X		X		

Issuing Date: 1-Jun-2008

Revision Date: 27-Mar-2015

SDS Number: 9199

Carbon Dioxide 124-38-9	X	X	X		-
----------------------------	---	---	---	--	---

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Methyl alcohol 67-56-1 (60 - 100)		Mexico: TWA= 200 ppm Mexico: TWA= 260 mg/m ³ Mexico: STEL= 250 ppm Mexico: STEL= 310 mg/m ³
Silane 7803-62-5 (3 - 7)	-	Mexico: TWA 5 ppm Mexico: TWA 7 mg/m ³
Carbon Dioxide 124-38-9 (1 - 5)	-	Mexico: TWA= 5000 ppm Mexico: TWA= 9000 mg/m ³ Mexico: STEL= 15000 ppm Mexico: STEL= 27000 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

A – Compressed gases

B5 – Flammable aerosol



16. Other Information

NFPA
HMIS

Health Hazards 2
Health Hazards 3*

Flammability 3
Flammability 4

Instability 0
Physical Hazard 0

Physical and Chemical Hazards -
Personal Protection X

Prepared By: Randy Boitz

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.