

SAFETY DATA SHEET

Issuing Date April 26, 2018

Revision Date N/A

Revision Number 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Rain-x -30

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Windshield Deicer - NonAerosol

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier NameHighline AftermarketSupplier Address4500 Malone Road

Memphis, TN 38118

US

Phone:800 648 4393

Supplier Phone Number Fax:336-398-5680

Contact Phone479-254-8636 nikki.lytle@cox-internet.com

Supplier Email

Emergency telephone number

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 3
Acute toxicity - Dermal	Category 3
Acute toxicity - Inhalation (Vapors)	Category 3
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 3

GHS Label elements, including precautionary statements

Page 1 / 13



Emergency Overview

Signal word

Danger

Hazard Statements

Toxic if swallowed
Toxic in contact with skin
Toxic if inhaled
Causes damage to organs
May cause damage to organs through prolonged or repeated exposure
Flammable liquid and vapor



Appearance Purple Physical State Liquid Odor Mild Ammonia

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Wear protective gloves/protective clothing/eye protection/face protection Use only outdoors or in a well-ventilated area Do not breathe dust/fume/gas/mist/vapors/spray Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ ventilating/ lighting/ equipment Use only non-sparking tools
Take precautionary measures against static discharge Keep cool

Precautionary Statements - Response

Specific treatment (see .? on this label)
Specific measures (see .? on this label)
IF exposed: Call a POISON CENTER or doctor/physician
Specific treatment (see supplemental first aid instructions on this label)

Skin

Call a POISON CENTER or doctor/physician if you feel unwell Wash contaminated clothing before reuse IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Rinse mouth

Fire



In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0.00406% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Harmful to aquatic life with long lasting effects

PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

A ACTIBODITION INTERNATION AND MARKETINE	^	AAMBAAITIAN IINEABHATIAN	ALI ILIABEBIELITA
--	---	--------------------------	-------------------

Chemical Name	CAS No	Weight-%	Trade Secret
Methyl alcohol	67-56-1	15 - 40	*
Ethylene glycol	107-21-1	1 - 5	*
Ammonium hydroxide	1336-21-6	0.1 - 1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical

attention is required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Keep eye wide open while rinsing. Do not rub affected area. Seek immediate medical attention/advice. Remove contact lenses, if present and easy

to do. Continue rinsing.

Skin Contact Immediate medical attention is required. Wash off immediately with soap and

plenty of water while removing all contaminated clothes and shoes.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Avoid direct contact

with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult,

(trained personnel should) give oxygen.

Ingestion Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water.

Never give anything by mouth to an unconscious person. Call a physician or



poison control center immediately.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take

precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Coughing and/ or wheezing. Difficulty in breathing. **Effects**

Indication of any immediate medical attention and special treatment needed

Notes to Dhysician Troot symptomotically

Suitable Extinguishing Media

5. FIRE-FIGHTING MEASURES

Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Vapors can form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

Uniform Fire Code Toxic: Liquid

Flammable Liquid: I-C

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.



6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Full encapsulating, vapor protective clothing should be worn for

spills and leaks with no fire. Stop leak if you can do it without risk.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental Precautions

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for Containment A vapor suppressing foam may be used to reduce vapors. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal.

Methods for cleaning up

Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for

later disposal. Soak up with inert absorbent material. Pick up and transfer to properly

labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Do not breathe vapor or mist. Use only with adequate ventilation and in closed systems. Use personal protection equipment. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding

connection when transferring this material to prevent static discharge, fire or explosion. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers.

Use according to package label instructions.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach

of children. Protect from moisture. Store away from other materials. Store locked up. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular

national regulations. Store in accordance with local regulations.

Incompatible Products None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters



Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methyl alcohol 67-56-1	STEL = 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m³ STEL: 325 mg/m³ STEL: 250 ppm
Ethylene glycol 107-21-1	Ceiling: 100 mg/m³ aerosol only	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m³	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection None required for consumer use. If splashes are likely to occur:. Tight sealing safety

goggles.

Skin and Body Protection None required for consumer use. If there is a risk of contact:. Wear protective gloves and

protective clothing. Antistatic boots.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or

smoke when using this product. Wash hands before breaks and immediately after handling the product. Take off contaminated clothing and wash before reuse. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment,

work area and clothing is recommended. Do not breathe vapor or mist.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical StateLiquidAppearancePurpleOdorMild Ammonia

Color No information available Odor Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks Method</u>

None known Melting / freezing point No data available None known Boiling point / boiling range 78 °C / 172 °F None known Flash Point 29 C / 84 F None known **Evaporation Rate** No data available None known Flammability (solid, gas) No data available None known

Flammability Limit in Air
Upper flammability limit
No data available



Lower flammability limit No data available

Vapor pressure No data available None known Vapor density No data available None known **Specific Gravity** No data available None known **Water Solubility** Miscible in water None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known Autoignition temperature No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known Dynamic viscosity No data available None known

Explosive properties

Oxidizing Properties

No data available
No data available

Other Information

Softening Point

VOC Content (%)

Particle Size

Particle Size Distribution

No data available
No data available

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Excessive heat. Heat, flames and sparks.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Toxic by inhalation. (based

on components).

Eye Contact Specific test data for the substance or mixture is not available.

Skin Contact Specific test data for the substance or mixture is not available. Toxic in contact with skin.

May be absorbed through the skin in harmful amounts. (based on components).

Ingestion Specific test data for the substance or mixture is not available. Harmful if swallowed. (based

on components).

Component Information



Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl alcohol 67-56-1	= 5628 mg/kg (Rat)	-	= 83.2 mg/L (Rat) 4 h
Ethylene glycol 107-21-1	= 4000 mg/kg (Rat)	-	-
Ammonium hydroxide 1336-21-6	= 350 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms Coughing and/ or wheezing. Difficulty in breathing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity Contains no ingredient listed as a carcinogen.

Reproductive Toxicity No information available.

STOT - single exposure Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29

CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). If this product is a mixture, the classification is not based

on toxicology studies for this product, but is based solely on toxicology studies for

ingredients found within this product. Detailed substance and/or ingredient information may be provided in other sections of this SDS. Target organs effects listed in this document may result from a single overexposure to this product. Causes damage to organs if swallowed.

Causes damage to organs in contact with skin.

STOT - repeated exposureCauses damage to organs through prolonged or repeated exposure. Based on

classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from

chronic or repeated exposure. (STOT RE).

Chronic Toxicity No known effect based on information supplied. Effects from this product caused by acute

exposure may cause permanent damage to target organs and/or may cause chronic conditions. Avoid repeated exposure. Prolonged exposure may cause chronic effects.

Target Organ Effects Respiratory system. Systemic Toxicity. Central Nervous System (CNS). Eyes.

Gastrointestinal tract (GI). Skin. Heart. Kidney.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
292.00 mg/kg
ATEmix (dermal)
891.00 mg/kg (ATE)
ATEmix (inhalation-dust/mist)
1.49 mg/l
ATEmix (inhalation-vapor)



Revision Date 09-Apr-2015 Rain-x -30

9.00 ATEmix

12. ECOLOGICAL INFORMATION

<u>Ecotoxicity</u> Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Methyl alcohol 67-56-1		96h LC50: = 28200 mg/L (Pimephales promelas) 96h LC50: > 100 mg/L (Pimephales promelas) 96h LC50: 19500 - 20700 mg/L (Oncorhynchus mykiss) 96h LC50: 18 - 20 mL/L (Oncorhynchus mykiss) 96h LC50: 13500 - 17600 mg/L (Lepomis macrochirus)	EC50 = 43000 mg/L 5 min	
Ethylene glycol 107-21-1	96h EC50: 6500 - 13000 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 41000 mg/L (Oncorhynchus mykiss) 96h LC50: 14 - 18 mL/L (Oncorhynchus mykiss) 96h LC50: = 40761 mg/L (Oncorhynchus mykiss) 96h LC50: = 27540 mg/L (Lepomis macrochirus) 96h LC50: = 16000 mg/L (Poecilia reticulata) 96h LC50: 40000 - 60000 mg/L (Pimephales promelas)	EC50 = 620.0 mg/L 30 min	48h EC50: = 46300 mg/L
Ammonium hydroxide 1336-21-6		96h LC50: = 8.2 mg/L (Pimephales promelas)		48h EC50: = 0.66 mg/L

Persistence and Degradability No information available.

Bioaccumulation

Chemical Name	Log Pow
Methyl alcohol 67-56-1	-0.77
Ethylene glycol 107-21-1	-1.93

Other adverse effects
No information available.



13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl alcohol		Included in waste stream:		U154
67-56-1		F039		

California Hazardous Waste Codes 212

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Methyl alcohol	Toxic
67-56-1	Ignitable
Ammonium hydroxide	Toxic
1336-21-6	Corrosive

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name CONSUMER COMMODITY

Hazard Class 3

Description CONSUMER COMMODITY, ORM-D

Emergency Response Guide 131

Number

TDG

UN-No. UN1986

Proper Shipping Name ALCOHOLS, FLAMMABLE, TOXIC, N.O.S.

Hazard Class 3
Subsidiary class (6.1)
Packing Group

Description UN1986, ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (METHYL ALCOHOL, AMMONIUM

HYDROXIDE), 3(6.1), III

MEX

UN-No. UN1986

Proper Shipping Name ALCOHOLS, FLAMMABLE, TOXIC, N.O.S.

Hazard Class 3
Subsidiary class 6.1
Packing Group III

Description UN1986 ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (METHYL ALCOHOL, AMMONIUM

HYDROXIDE), 3(6.1), III

<u>ICAO</u>

UN-No. UN1986

Proper Shipping Name ALCOHOLS, FLAMMABLE, TOXIC, N.O.S.

Hazard Class 3 Subsidiary class 6.1



Revision Date 09-Apr-2015 Rain-x -30

Packing Group

Description UN1986, ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (METHYL ALCOHOL, AMMONIUM

HYDROXIDE), 3(6.1), III

IATA

UN1986 UN-No.

ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. **Proper Shipping Name**

Hazard Class 6.1 **Subsidiary class** Ш **Packing Group**

UN1986, ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (METHYL ALCOHOL), 3 (6.1), III Description

IMDG/IMO

UN1986 UN-No.

ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. **Proper Shipping Name**

Hazard Class 6.1 **Subsidiary class** Ш **Packing Group** F-E. S-D EmS-No.

UN1986, ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (METHYL ALCOHOL), 3 (6.1), III, FP Description

29C

RID

UN1986 UN-No.

ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. **Proper Shipping Name**

Hazard Class Ш **Packing Group** FT1 Classification code

UN1986 ALCOHOLS, FLAMMABLE, TOXIC, N.O.S.(METHYL ALCOHOL, AMMONIUM Description

HYDROXIDE), 3(6.1), III

6.1 ADR/RID-Labels

ADR

UN1986 UN-No.

ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. **Proper Shipping Name**

Hazard Class Ш Packing Group FT1 Classification code

UN1986 ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (METHYL ALCOHOL, AMMONIUM Description

HYDROXIDE), 3(6.1), III

6.1 ADR/RID-Labels

ADN

UN1986

UN-No. ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. **Proper Shipping Name**

3 **Hazard Class** Ш **Packing Group** FT1 Classification code 274, 802

Special Provisions UN1986 ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (METHYL ALCOHOL, AMMONIUM Description

HYDROXIDE), 3(6.1), III

3 + 6.1**Hazard Labels** 5 L **Limited Quantity**

VE01, VE02 Ventilation

15. REGULATORY INFORMATION

International Inventories

TSCA

DSL All components are listed either on the DSL or NDSL.



TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Methyl alcohol - 67-56-1	67-56-1	15 - 40	1.0
Ethylene glycol - 107-21-1	107-21-1	1 - 5	1.0
Ammonium hydroxide - 1336-21-6	1336-21-6	0.1 - 1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard
Yes
Chronic Health Hazard
Yes
Fire Hazard
Yes
Sudden release of pressure hazard
No
Reactive Hazard
No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ammonium hydroxide 1336-21-6	1000 lb			Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Methyl alcohol 67-56-1	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ
Ethylene glycol 107-21-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Ammonium hydroxide 1336-21-6	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65	
C.I. Food red 15 - 81-88-9	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Methyl alcohol 67-56-1	Х	Х	Х	Х	Х
Ethylene glycol 107-21-1	Х	Х	X	Х	Х
Ammonium hydroxide 1336-21-6	X	Х	Χ	Х	

Page 12 / 13



International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Methyl alcohol		Mexico: TWA= 200 ppm
67-56-1 (15 - 40)		Mexico: TWA= 260 mg/m ³
		Mexico: STEL= 250 ppm
		Mexico: STEL= 310 mg/m ³
Ethylene glycol		Mexico: Ceiling 100 mg/m ³
107-21-1 (1 - 5)		

Mexico - Occupational Exposure Limits - Carcinogens

Canada WHMIS Hazard Class B2 - Flammable liquid



16. OTHER INFORMATION

NFPA Health Hazards 3 Flammability 3 Instability 0 Physical and Chemical Hazards -

HMIS Health Hazards 3 * Flammability 3 Physical Hazard 0 Personal Protection

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

29-May-2013 09-Apr-2015

Revision Note No information available

Disclaimer

Issuing Date Revision Date

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet