

ZECO20124 – ISOPROPYL FUEL LINE ANTIFREEZE

SECTION 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product name Product number Brand ISOPROPYL Fuel Line Antifreeze ZECO20124 Zecol

1.4 SUPPLIER'S DETAILS Name Address

> Telephone email

Highline Aftermarket 4500 Malone Road Memphis TN 38118 901-775-5555 sds@highlineaftermarket.com

1.5 EMERGENCY PHONE NUMBER

CHEM-TEL (800) 255-3924 24 Hour Assistance

SECTION 2: HAZARD IDENTIFICATION

General hazard statement

"Consumer Products", as defined by the US Consumer Product Safety Act and which are used as intended (typical consumer duration and frequency), are exempt from the OSHA Hazard Communication Standard (29 CFR 1910.1200). This SDS is being provided as a courtesy to help assist in the safe handling and proper use of the product.

2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS classification in accordance with: (US) OSHA (29 CFR 1910.1200)

- Specific target organ toxicity (single exposure), Cat. 1
- Acute toxicity, dermal, Cat. 5
- Acute toxicity, inhalation, Cat. 4
- Acute toxicity, inhalation, Cat. 5
- Acute toxicity, oral, Cat. 4
- Flammable liquids, Cat. 3
- Eye damage/irritation, Cat. 2A
- Specific target organ toxicity (single exposure), Cat. 3

2.2 GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

Pictogram



Signal word

Warning





Hazard statement(s) H226 H302 H319 H331	Flammable liquid and vapor Harmful if swallowed Causes serious eye irritation Toxic if inhaled
Precautionary statement(s) P210 P233 P240 P241 P242 P243 P260 P261 P264 P270 P271 P280 P301+P312 P302+P352 P303+P361+P353 P304+P340 P305+P351+P338 P308+P311 P312 P330 P337+P313 P361+P364 P370+P378 P403+P233	 Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection/protective gloves/protective clothing. IF SWALLOWED: Call a POISON CENTER /doctor if you feel unwell, IF ON SKIN: Wash with plenty of water IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF Exposed or concerned: Call a POISON CENTER/doctor Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. If eye irri
P403+P235 P405 P501	Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container to proper receptacle.

2.3 Other hazards which do not result in classification

Can cause eye and skin irritation. HARMFUL IF SWALLOWED. DANGER! POISON! CANNOT BE MADE NONPOISONOUS. Irritation to respiratory tract. Can cause blindness.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 MIXTURES

Hazardous components

1. Isopropyl alcohol

Concentration	100 % (weight)
EC no.	414-810-0
CAS no.	67-63-0



Index no.

607-403-00-6

- Flammable liquids, Cat. 2

- Eye damage/irritation, Cat. 2A
- Specific target organ toxicity (single exposure), Cat. 3

H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

SECTION 4: FIRST-AID MEASURES

4.1 DESCRIPTION OF NECESSARY FIRST-AID MEASURES

If inhaled	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
	Acute and delayed symptoms and effects: May cause drowsiness or dizziness. May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain
	Remove person to fresh air. If you feel unwell, get medical attention.
In case of skin contact	Take off immediately all contaminated clothing. Wash with plenty of soap and water for at least 15 minutes. Get medical attention if irritation develops or persists. Wash contaminated clothing before reuse.
	Acute and delayed symptoms and effects: May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching.
In case of eye contact	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, get medical attention
	Acute and delayed symptoms and effects: May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.
If swallowed	Rinse mouth. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Call a poison center or doctor immediately.
	Acute and delayed symptoms and effects: Harmful if swallowed. May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

4.2 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED



The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 SUITABLE EXTINGUISHING MEDIA

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

- 5.2 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL Methanol: Carbon oxides
- 5.3 SPECIAL PROTECTIVE ACTIONS FOR FIRE-FIGHTERS Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Use water spray to cool unopened containers.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

6.2 ENVIRONMENTAL PRECAUTIONS

Do not let product enter drains.

6.3 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Eliminate all sources of ignition. Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

Reference to other sections

For disposal see section 13.

SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Wash hands with soap and water after handling. Container explosion may occur under fire conditions. Use explosion-proof equipment. Keep away from sources of ignition. No smoking. Take measures to prevent the build-up of electrostatic charge. For precautions see section 2.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Keep container tightly closed in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Specific end use(s)

Apart from the uses mentioned in section 1 no other specific uses are stipulated.



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

1. Isopropyl alcohol (CAS: 67-63-0)

PEL (Inhalation): 400 ppm (OSHA) OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 980 mg/m3 (OSHA) OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 400 ppm, (ST) 500 ppm (Cal/OSHA) OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 400 ppm, (ST) 500 ppm (NIOSH) OSHA Annotated Table Z-1, www.osha.gov

TLV® (Inhalation): 200 ppm, (ST) 400 ppm; USA (ACGIH) OSHA Annotated Table Z-1, www.osha.gov

8.2 APPROPRIATE ENGINEERING CONTROLS

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, gas, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT (PPE)

Pictograms



Eye/face protection

Tightly fitting safety goggles. If splash hazard, wear faceshield (8-inch minimum). Use equipment for eye protection that meets the standards referenced by OSHA regulations in 29 CFR 1910.133 for Personal Protective Equipment.

Skin protection

Wear protective gloves, such as nitrile gloves.

Body protection

The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Not required under normal use conditions. If engineering controls and ventilation are not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator with organic vapor/acid gas cartridge and particulate filter, or self-contained breathing apparatus must be used. Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators.

Thermal hazards

No data available.

Environmental exposure controls



Do not let product enter drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance/form (physical state, color, etc.) Odor Odor threshold pH Melting point/freezing point Initial boiling point and boiling range Flash point Evaporation rate Flammability (solid, gas) Upper/lower flammability limits

Upper/lower explosive limits Vapor pressure Vapor density Relative density Solubility(ies) Partition coefficient: n-octanol/water Auto-ignition temperature Decomposition temperature Viscosity Explosive properties Oxidizing properties Clear Liquid Mild No data available. 7.0-8.0 No data available. No data available. No data available No data available. 2.5% Lower 12% Upper No data available.

0.79 No data available. No data available. 750.2F No data available. No data available. No data available. No data available.

No data available.

Other safety information

SECTION 10: STABILITY AND REACTIVITY

10.1 REACTIVITY

This material is considered to be nonreactive under normal use conditions.

10.2 CHEMICAL STABILITY

Stable under normal storage conditions.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS No data available.

10.4 CONDITIONS TO AVOID

Heat, flames and sparks. Incompatible products. Keep away from open flames, hot surfaces and sources of ignition.

10.5 INCOMPATIBLE MATERIALS

Methanol: Acid chlorides, Acid anhydrides, Oxidizing agents, Alkali metals, Reducing agents, Acids

Isopropanol: Oxidizing agents, Acid anhydrides, Aluminium, Halogenated compounds, Acids



10.6 HAZARDOUS DECOMPOSITION PRODUCTS

No data available.

Isopropanol: Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity

Components:

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion. Acute and delayed symptoms and effects from inhalation, skin and eye contact and ingestion are listed in Section 4.

ATE (dermal) of mixture: 2500 mg/kg ATE (inhalation, gaseous) of mixture: 5833.33 ppmv ATE (inhalation, vapor) of mixture: 25 mg/l ATE (oral) of mixture: 833.33 mg/kg

Skin corrosion/irritation

May cause skin irritation.

Serious eye damage/irritation

May cause eye irritation.

Respiratory or skin sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH,NTP, or EPA classification

Reproductive toxicity

Suspected of damaging fertility or the unborn child

STOT-single exposure May cause drowsiness or dizziness

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure

Aspiration hazard

May be harmful if swallowed and enters airways



SECTION 12: ECOLOGICAL INFORMATION

Toxicity No data available on product

Persistence and degradability No data available on product

Bioaccumulative potential No data available on product

Mobility in soil No data available on product.

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects

No data available on product.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal of the product

Disposal should be in accordance with applicable Federal, State and local laws and regulations. Local regulations may be more stringent than State or Federal requirements.

Disposal of contaminated packaging

Dispose of as unused product.

SECTION 14: TRANSPORT INFORMATION

DOT (US)

UN Number: UN1219 Class: 3 Packing Group: II Proper Shipping Name: Isopropyl Alcohol Reportable quantity (RQ): Marine pollutant: Poison inhalation hazard:

SECTION 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS SPECIFIC FOR THE PRODUCT IN QUESTION

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.



Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

Isopropyl alcohol CAS number: 67-63-0

New Jersey Right To Know Components

No components are subject to the New Jersey Right to Know Act.

Isopropyl alcohol CAS number: 67-63-0

Pennsylvania Right To Know Components

No components are subject to the Pennsylvania Right to Know Act.

Isopropyl alcohol CAS number: 67-63-0

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

The following components are subject to reporting levels established by SARA Title III, Section 313: Isopropyl alcohol CAS number: 67-63-0

SECTION 16: OTHER INFORMATION

16.1 FURTHER INFORMATION/DISCLAIMER

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. In no event shall Highline Aftermarket be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if Highline Aftermarket has been advised of the possibility of such damages.

Prepared By Mark Kozak